





**GLUE DOWN**  
luxury vinyl tile



Embossed Wearlayer  
with PU finishing

Design film  
Comfort layer



**No limits  
on installation  
& no joints  
needed.**



CLASS 32



GLUE  
DOWN



OK RADIANT  
HEATING



ULTRA  
THIN



WATER  
PROOF

COLLECTIONS	ORIGINALS	XL SLATE	STONE	TREND
Dimensions EN 427	1212 x 222 x 2 mm	1212 x 452 x 2 mm	622 x 452 x 2 mm	1212 x 222 x 1,5 mm
Emboss / Surface	Deep Wood Super-matte	Regular Slate Semi-matte	Regular Stone Semi-matte	Regular Wood Semi-matte
Class EN 649	32	32	32	32
Weight EN 430	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>
Impact Sound Reduction EN 140	4 dB	4 dB	4 dB	4 dB
Dimensional Stability en 434		Approved		
Fire Resistance EN 131501		Bfl - S1		
Chemical Resistance EN 423		Class 0 - Good		
Abrasion Wear EN 425		Pass Castor Chair (W)		
Slippery Resistance		DIN 51133 - Class R9 EN 13893 - Class DS		
Indentation EN 433		max 0,08mm		
Anti-static Resistance EN 1815		< 2kV		
Toxicity EN 71		Non Toxic		
Resistance to Fading ISO 105 B02		6/8 Good		
AbBB/Dibt low VOC (U-Sign)		Certified		
Thermal Resistance EN 12524		0,036 m <sup>2</sup> K/W		
Underfloor Heating		Approved 27°C		
Thermal Conductivity EN 12667		10.076 w(m-k)		



UNICLIC

