



RIGID CLICK

water proof flooring




Embossed Wearlayer
with PU finishing

Design film

100% Waterproof Solid Board

Comfort & Acoustic IXPE underlay



Perfect for big areas
 up to 400m² without
 joints. Water proof
 floating floors
 to fit allspaces.



CLASS **33** / **42**



EASY
TO INSTALL



OK RADIANT
HEATING



STRONG CARRIER
BOARD



ULTRA
THIN



WATER
PROOF

COLLECTION	LUNGO SENSES	LUNGO	EXTENDEDSENSES	METROPOLITAN	SCANDINAVIAN
Dimensions EN 427	1800 x 228 x 6,0mm <small>(including 1mm underlay IXPE)</small>	1800 x 228 x 6,0mm <small>(including 1mm underlay IXPE)</small>	1500 x 228 x 6,0mm <small>(including 1mm underlay IXPE)</small>	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>
Emboss / Surface	Registered Wood Emboss Semi-Matte	Regular Wood Emboss Semi-matte	Registered Wood Emboss Semi-Matte	Regular Wood Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 16511	33	33	33	33	33
Weight EN 430	10,1kg/m ²	10,1kg/m ²	10,1kg/m ²	9,1kg/m ²	9,1kg/m ²
Dimensional Stability EN 434			0,10%		
Fire Resistance EN 131501			Bfl - S1		
Chemical Resistance EN 423			Class 0 - Good		
Abrasion Wear EN 425			Pass Castor Chair (W)		
Slippery Resistance			DS (R9 very secure)		
Indentation EN 433			max 0,03mm		
Anti-static Resistance EN 1815			< 2kV		
Toxicity EN 71			Non Toxic		
Resistance to Fading ISO 105 B02			6/8 depending on design		
AbBB/Dibt low VOC (U-Sign)			Certified		
Thermal Resistance EN 12524			0,032 m2K/W		
Underfloor Heating			Approved 27°C		
Wet Areas			Approved		



UNICLIC

