




RIGID CLICK PLUS

water proof flooring



Embossed Wearlayer
with PU finishing
Design film
Comfort Layer
100% Waterproof Solid Board
Comfort & Acoustic IXPE underlay



**Superior comfort
for wet areas.
Perfect for big areas
up to 400 m²
without joints.**



CLASS **33** / **42**



EASY TO INSTALL



OK RADIANT HEATING



STRONG CARRIER BOARD



ULTRA THIN



WATER PROOF

COLLECTION	LUNGO SENSES	LUNGO	EXTENDEDSENSES	METROPOLITAN	SCANDINAVIAN
Dimensions EN 427	1805 x 225 x 6,5mm <small>(including 1mm underlay IXPE)</small>	1805 x 225 x 6,5mm <small>(including 1mm underlay IXPE)</small>	1505 x 225 x 6,5mm <small>(including 1mm underlay IXPE)</small>	1205 x 215 x 5,7mm <small>(including 1mm underlay IXPE)</small>	1205 x 215 x 5,7mm <small>(including 1mm underlay IXPE)</small>
Emboss / Surface	Registered Wood Emboss Semi-Matte	Regular Wood Emboss Semi-matte	Registered Wood Emboss Semi-Matte	Regular Wood Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 16511	33	33	33	33	33
Weight EN 430	11,1kg/m ²	11,1kg/m ²	11,1kg/m ²	10,1kg/m ²	10,1kg/m ²
Dimensional Stability EN 434			0.1%		
Effect of a castor chair ISO 4918			25.000 cycles no delamination		
Abrasion Resistance EN 660-2			Group T		
Resistance against impact (big ball) EN 13329			no visible change		
Residual Indentation EN 433			≤ 0.2mm		
Fire Resistance DIN EN 13501			Bfl -s1		
Anti-sliding properties EN13893			Class DS		
Slip Resistance DIN 51130			> R9		
Formaldehyde emission EN 717-1			E1		
Emission Values			In accordance to AgBB		
Content of PCP			Not to declare		
Thermal Resistance EN 12667			0.032 m ² K/W		
Chemical Resistance EN 423			Class 0, Excellent		
Color Fastness ISO 105-B02			Minimum 6		
Wet areas			Approved		
Underfloor heating			Approved 27 C		
Locking strength ISO 24334			short side joints: 2.0 kN/m long side joints 1.32 kN/m		
Resistance to Fading ISO 105 B02			6/8 Good		



UNICLIC

