




F FLOATING
 eco friendly
 floating floor



Top coating for residential
 or commercial areas
 Design layer
 High-density fiberboard
 Comfort cork backing
 Cork granulate underlayment



**Unique design
 options for cork
 flooring**



CLASS 31



COLLECTIONS	ENZO
Dimensions EN 427	1200 x 210 x 10,5 mm
Classification EN 16511	31
Dimensional Stability EN 434	0.1%
Castor chair EN 425	no visible change
Effect of a furniture leg EN 424	no visible change / damages
Resistance against impact (big ball) EN 13329, Annex F	> 1800
Microscratch resistance DIN EN 16094	MSR-A1 / MSR-B3
Abrasion resistance EN 15468:2013, Annex A (Falling-Sand method)	5200 revolutions
Residual Indentation EN ISO 24343-1	0,14 mm
Fire Resistance DIN EN 13501	Cfl -s1
Anti-sliding properties EN 13893	DS
Anti-slip property DIN 51130:2014	R9
Formaldehyde emission EN 717-1	E1
Electrostatic behaviour EN 1815	Antistatic Floor Covering
Thermal Resistance EN 12667:2001	0,115 M2 k/W
Impact Sound Reduction EN 140	17 dB
Locking strength ISO 24334:2019-07	Short side joints 210mm / Long side joints 200mm
Impact Resistance EN 16511: 2014	> 1800
Light Fastness ISO 105-B02:2014-09	= 6 no change of colour
Pull of Strength EN ISO 4624:2016-04 (Method B)	1,02 MP a

