



RIGID CLICK

water proof flooring




Embossed Wearlayer
with PU finishing

Design film

100% Waterproof Solid Board

Comfort & Acoustic IXPE underlay



Perfect for big areas
 up to 400m² without
 joints. Water proof
 floating floors
 to fit all spaces.



CLASS 32



COLLECTION	ORIGINALS	XL SLATE	STONE	TREND
Dimensions EN 427	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>	1230 x 470 x 5,5mm <small>(including 1mm underlay IXPE)</small>	620 x 470 x 5,5mm <small>(including 1mm underlay IXPE)</small>	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>
Emboss / Surface	Deep Wood Emboss Super-matte	Regular Slate Emboss Semi-matte	Regular Stone Emboss Semi-matte	Regular Wood Emboss Semi-matte
Impact Sound Reduction EN 140	19 dB	19 dB	19 dB	19 dB
Class EN 16511	32	32	32	32
Weight EN 430	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²
Dimensional Stability EN 434	0,10%			
Fire Resistance EN 131501	Bfl - S1			
Chemical Resistance EN 423	Class 0 - Good			
Abrasion Wear EN 425	Pass Castor Chair (W)			
Slippery Resistance	DS (R9 very secure)			
Indentation EN 433	max 0,03mm			
Anti-static Resistance EN 1815	< 2kV			
Toxicity EN 71	Non Toxic			
Resistance to Fading ISO 105 B02	6/8 depending on design			
AbBB/Dibt low VOC (U-Sign)	Certified			
Thermal Resistance EN 12524	0,032 m ² K/W			
Underfloor Heating	Approved 27°C			
	Approved			

