




RIGID CLICK PLUS

water proof flooring



Embossed Wearlayer with PU finishing
 Design film
 Comfort Layer
 100% Waterproof Solid Board
 Comfort & Acoustic IXPE underlay



Superior comfort for wet areas.
 Perfect for big areas up to 400 m² without joints.



CLASS 32



COLLECTION	ORIGINALS	XL SLATE	STONE	TREND
Dimensions EN 427	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>	1230 x 470 x 5,5mm <small>(including 1mm underlay IXPE)</small>	620 x 470 x 5,5mm <small>(including 1mm underlay IXPE)</small>	1230 x 228 x 5,5mm <small>(including 1mm underlay IXPE)</small>
Emboss / Surface	Deep Wood Emboss Super-matte	Regular Slate Emboss Semi-matte	Regular Stone Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 16511	32	32	32	32
Weight EN 430	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²
Dimensional Stability EN 434	0.1%			
Effect of a castor chair ISO 4918	25.000 cycles no delamination			
Abrasion Resistance EN 660-2	Group T			
Resistance against impact (big ball) EN 13329	no visible change			
Residual Indentation EN 433	≤ 0.2mm			
Fire Resistance DIN EN 13501	Bfl -s1			
Anti-sliding properties EN13893	Class DS			
Slip Resistance DIN 51130	> R9			
Formaldehyde emission EN 717-1	E1			
Emission Values	In accordance to AgBB			
Content of PCP	Not to declare			
Thermal Resistance EN 12667	0.032 m ² K/W			
Chemical Resistance EN 423	Class 0, Excellent			
Color Fastness ISO 105-B02	Minimum 6			
Wet areas	Approved			
Underfloor heating	Approved 27 C			
Locking strength ISO 24334	short side joints: 2.0 kN/m long side joints 1.32 kN/m			
Resistance to Fading ISO 105 B02	6/8 Good			

