




F **FLOATING**
design floating floor



NATURAL SHIELD® water base urethane varnish
Natural cork decor
High-density fiberboard
Cork granulate underlayment



Comfortable living is not a luxury.



CLASS 23 / 32



ANTI-SLIPPERY



EASY TO INSTALL



EXTRA WARMTH & COMFORT



OK RADIANT HEATING



RESISTANT



SOUND REDUCTION

COLLECTIONS	EXCLUSIVE	ETHERNAL
Dimensions	900 x 300 x 11 mm	900 x 300 x 10 mm
Weight EN 430		8 Kg/m ²
Level of use Domestic		23
Level of use Commercial		31
Thickness EN 428		10 mm - 11 mm
Dimensions EN 427		900 x 300 mm
Dimensional Stability EN434		0.1%
Resistance against staining EN 438		Grade 1- 5
Resistance to scratching EN 438-2		4 N / Grade 3
Residual Indentation EN ISO 24343-1		0.13 mm
Fire Resistance DIN EN 13501		Cfl-s1
Anti-sliding properties EN13893		DS
Formaldehyde emission EN 717-1		E1
Thermal Resistance EN 12667		0.1 (m ² K)/W
Impact Sound Reduction EN 140		17 dB - 19dB
Impact Insulation Class IIC according ASTM E 492-09 / ASTM E 989-89		55 dB
Locking strength ISO 24334		-
Short side joints		4.8 kN/m
Long side joints		4.2 kN/m



UNICLIC

