



RIGID CLICK

water proof flooring




Embossed Wearlayer
with PU finishing

Design film

100% Waterproof Solid Board

Comfort & Acoustic IXPE underlay



Perfect for big areas
 up to 400m² without
 joints. Water proof
 floating floors
 to fit allspaces.



CLASS 32



COLLECTION	ORIGINALS	XL SLATE	STONE	TREND
Dimensions EN 427	1230 x 228 x 5,5mm (including 1mm underlay IXPE)	1230 x 470 x 5,5mm (including 1mm underlay IXPE)	620 x 470 x 5,5mm (including 1mm underlay IXPE)	1230 x 228 x 5,5mm (including 1mm underlay IXPE)
Emboss / Surface	Deep Wood Emboss Super-matte	Regular Slate Emboss Semi-matte	Regular Stone Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 16511	32	32	32	32
Weight EN 430	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²	9,1kg/m ²
Dimensional Stability EN 434			0,10%	
Fire Resistance EN 131501			Bfl - S1	
Chemical Resistance EN 423			Class 0 - Good	
Abrasion Wear EN 425			Pass Castor Chair (W)	
Slippery Resistance			DS (R9 very secure)	
Indentation EN 433			max 0,03mm	
Anti-static Resistance EN 1815			< 2kV	
Toxicity EN 71			Non Toxic	
Resistance to Fading ISO 105 B02			6/8 depending on design	
AbBB/Dibt low VOC (U-Sign)			Certified	
Thermal Resistance EN 12524			0,032 m ² K/W	
Underfloor Heating			Approved 27°C	
Wet Areas			Approved	

