





**GD** **GLUE DOWN**  
eco friendly floor tiles



NATURAL SHIELD®  
water base urthane varnish

Natural cork decor



**Comfortable  
living is not  
a luxury.**



CLASS 23 / 32



ANTI-SLIPPERY



EASY TO REPAIR



EXTRA WARMTH & COMFORT



GLUE DOWN



OK RADIANT HEATING



RESISTANT



SOUND REDUCTION

COLLECTIONS	EXCLUSIVE	ETHERNAL
Dimensions EN 427		600 x 300
Thickness EN 428		6 mm
Squareness EN 427		< 0,3 mm
Straightness EN 427		< 0,2 mm
Opening between panels EN 14085		-
Residual Indentation EN 433		< 0,25 mm
Dimension Stability EN 434		< 4%
Fire classification EN 13501-1		Cfl - S1
Formaldehyde emission EN 717-1/2		-
Determination of the Slippery resistance		Class DS
Impact Noise Reduction ISO 140-8		14 dB
Anti-static Resistance EN 1815		< 2k V




UNICLIC






**GD** **GLUE DOWN**  
 eco friendly floor tiles



High resistance  
**ULTRA SHIELD®**  
 water base urthane varnish

Natural cork decor



**Comfortable  
 living is not  
 a luxury.**



CLASS **23** / **32**



COLLECTIONS	EXCLUSIVE	ETHERNAL
Dimensions EN 427		600 x 300
Thickness EN 428		6 mm
Squareness EN 427		< 0,3 mm
Straightness EN 427		< 0,2 mm
Openingbetween panels EN 14085		-
Residual Indentation EN 433		< 0,25 mm
Dimension Stability EN 434		< 4%
Fire classification EN 13501-1		Cfl - S1
Formaldehyde emission EN 717-1/2		-
Determination of the Slippery resistance		Class DS
Impact Noise Reduction ISO 140-8		14 dB
Anti-static Resistance EN 1815		< 2k V